

CM421BL7CSSADA



32.5" x 19.25" x 21.38" (H x W x D)

Commercially listed ADA compliant 20" wide built-in refrigerator-freezer in complete stainless steel with a lock and towel bar handle

Highlights:

ETL-S listed for commercial use

32" height fits under lower ADA compliant counters

Flexible design allows built-in or freestanding use in 20" wide spaces

Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use	
ADA compliant	32" high to fit under lower ADA compliant counters	
Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint	
Built-in capable	Make the best use of space by installing your appliance under the counter	
Factory installed lock	Top-mounted for convenient security	
Fully finished cabinet	Allows the unit to be used freestanding	
Complete stainless steel exterior	Fully wrapped in 304 grade stainless steel	
Professional towel bar handle	A curved stainless steel handle provides generous room for a comfortable grip	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	

 \checkmark





CM421BL7CSSADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.5" (83 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	4.1 cu.ft. (116 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	72.0 lbs. (33 kg)
Shipping Weight	75.0 lbs. (34 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101038964
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Adjustable Shelves	Yes
Crisper Qty	1
Crisper Finish	Transparent
Crisper Cover	Glass
Interior Light	Yes
Refrigerator - Interior Height	28.75" (73 cm)
Refrigerator - Interior Width	15.75" (40 cm)
Refrigerator - Interior Depth	17.75" (45 cm)
Refrigerator - Shelf Type	Glass
Refrigerator - Shelf Qty	2
	Dial
Thermostat Type	Diai
Thermostat Type Refrigerant Type	R134a

High Side PSI	205.0
Low Side PSI	103.0
Level Legs	2
Wheels	2



